



## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2010

Revision: 25.01.2010

### 1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** 6.09 ZWALUW MONTAGEFIX-PU
- **Article number:** PU59
- **Application of the substance / the preparation** Adhesives
- **Manufacturer/Supplier:**  
DEN BRAVEN SEALANTS BV  
Denariusstraat 11  
4903 RC Oosterhout  
Netherlands  
Tel: +31 (0)162-491000  
Fax: +31 (0)162-421217  
E-mail: info@denbraven.nl  
Internet: www.denbraven.nl
- **Further information obtainable from:**  
Product safety department.  
info@denbraven.nl
- **Information in case of emergency:**  
info@denbraven.nl  
Tel.: +31 (0)162-491000

### 2 Hazards identification

- **Hazard description:**



Xn Harmful

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 36/37/38 Irritating to eyes, respiratory system and skin.

R 42/43 May cause sensitisation by inhalation and skin contact.

Contains isocyanates. See information supplied by the manufacturer

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

### 3 Composition/information on ingredients

- **Chemical characterization**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 9016-87-9 EINECS: 202-966-0	4,4'-methylenediphenyl diisocyanate Carc. Cat. 3;  Xn,  Xi; R 20-36/37/38-42/43	10-30%
CAS: 872-50-4 EINECS: 212-828-1	N-methyl-2-pyrrolidone Xi; R 36/38	1-5%
CAS: 77-58-7 EINECS: 201-039-8	dibutyltin dilaurate Muta. Cat. 3, Repr. Cat. 2;  T,  N; R 60-61-48/25-68-50/53	≤1.0%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

GB

(Contd. on page 2)



## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2010

Revision: 25.01.2010

Trade name: 6.09 ZWALUW MONTAGEFIX-PU

(Contd. of page 1)

### 4 First aid measures

- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

### 5 Fire-fighting measures

- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Person-related safety precautions:** Ensure adequate ventilation
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**  
Pick up mechanically.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.

### 7 Handling and storage

- **Handling:**
- **Information for safe handling:** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:** No special measures required.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

### 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**


**9016-87-9 diphenylmethanediisocyanate, isomeres and homologues (10-30%)**

WEL	Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO
-----	---

**872-50-4 N-methyl-2-pyrrolidone (5-10%)**

WEL	Short-term value: 309 mg/m <sup>3</sup> , 75 ppm Long-term value: 103 mg/m <sup>3</sup> , 25 ppm Sk
-----	---

(Contd. on page 3)



## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2010

Revision: 25.01.2010

Trade name: 6.09 ZWALUW MONTAGEFIX-PU

(Contd. of page 2)

**77-58-7 dibutyltin dilaurate ( $\leq 1.0\%$ )**

WEL	Short-term value: 0.2 mg/m <sup>3</sup> Long-term value: 0.1 mg/m <sup>3</sup> as Sn; Sk
-----	--

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

### 9 Physical and chemical properties

#### · General Information

<b>Form:</b>	Pasty
<b>Colour:</b>	Beige
<b>Odour:</b>	Characteristic

#### · Change in condition

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** 190°C

· **Flash point:** > 55°C

· **Ignition temperature:** 270°C

· **Self-igniting:** Product is not selfigniting.

(Contd. on page 4)



## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2010

Revision: 25.01.2010

Trade name: 6.09 ZWALUW MONTAGEFIX-PU

(Contd. of page 3)

· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Explosion limits:</b>	
<b>Lower:</b>	Undetermined.
<b>Upper:</b>	Undetermined.
· <b>Vapour pressure:</b>	Undetermined.
· <b>Density at 20°C:</b>	1.46 g/cm <sup>3</sup>
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>pH-value:</b>	Undetermined.
· <b>Solvent content:</b>	
<b>VOC (EC)</b>	6.00 %
<b>VOC (EC)</b>	87.6 g/l

### 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Materials to be avoided:**
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:**
  - Isocyanate
  - Carbon monoxide and carbon dioxide
  - Nitrogen oxides

### 11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

77-58-7 dibutyltin dilaurate

Oral | LD50 | 175 mg/kg (rat)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

- **Sensitization:**

Sensitization possible through inhalation.  
Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

- **Sensitisation** May cause sensitisation by inhalation and skin contact.

### 12 Ecological information

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 5)



## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2010

Revision: 25.01.2010

**Trade name: 6.09 ZWALUW MONTAGEFIX-PU**

(Contd. of page 4)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### 13 Disposal considerations

- **Product:**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 04 09	waste adhesives and sealants containing organic solvents or other dangerous substances
----------	--

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **Land transport ADR/RID (cross-border)**

- **ADR/RID class:** -

- **Maritime transport IMDG:**

- **IMDG Class:** -

- **Air transport ICAO-TI and IATA-DGR:**

- **ICAO/IATA Class:** -

### 15 Regulatory information

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

- **Code letter and hazard designation of product:**



Xn Harmful

- **Hazard-determining components of labelling:**

4,4'-methylenediphenyl diisocyanate

- **Risk phrases:**

36/37/38 Irritating to eyes, respiratory system and skin.

42/43 May cause sensitisation by inhalation and skin contact.

- **Safety phrases:**

2 Keep out of the reach of children.

23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

24 Avoid contact with skin.

37 Wear suitable gloves.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

56 Dispose of this material and its container to hazardous or special waste collection point.

63 In case of accident by inhalation: remove casualty to fresh air and keep at rest.

(Contd. on page 6)



**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.01.2010

Revision: 25.01.2010

**Trade name: 6.09 ZWALUW MONTAGEFIX-PU**

(Contd. of page 5)

· **Special labelling of certain preparations:**

Contains isocyanates. See information supplied by the manufacturer

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

- 20 Harmful by inhalation.
- 36/37/38 Irritating to eyes, respiratory system and skin.
- 36/38 Irritating to eyes and skin.
- 42/43 May cause sensitisation by inhalation and skin contact.
- 48/25 Toxic: danger of serious damage to health by prolonged exposure if swallowed.
- 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 60 May impair fertility.
- 61 May cause harm to the unborn child.
- 68 Possible risk of irreversible effects.

· **Department issuing MSDS:** Product safety department.

· **Contact:** Mr. C.J.A. Timmermans

GB